



RETAINING WALL SYSTEM



**BAINES
MASONRY**
Quality First

Norfolk[®] Wall System

Australian Owned, Designed and Manufactured

PRODUCT INFORMATION

Norfolk® Wall System

**Choose the original Norfolk® block -
Beware of imitations!**

Economic to build
No mortar required
Do It Yourself
Structurally Sound
Low Maintenance



Norfolk® Wall Block
390mm x 190mm x 180mm
1 sqm = 14 blocks
Approx. 18 kg each
90 per pallet
Code 020-144



Norfolk® Capping Block
390mm x 190mm x 180mm
1 lineal m = 2.56 blocks
Approx. 22 kg each
90 per pallet
Code 020-146



Retaining Wall Designer Available
visit www.retainingwalldesigner.com.au

Complies with AS 4678

PLEASE NOTE: For Norfolk Walls over 800mm high, please seek specific engineering advice!


CALCULATING BLOCK QUANTITIES

20 metres long x 0.9m high = 18m ² x 14 blocks per m ²	= 252 blocks
LESS 20 lineal meters x 2.56 capping blocks per metre	= 52 Capping blocks required overall
Blocks required to complete job	= 200 Norfolk Blocks + 52 Norfolk Capping Blocks

FINISH AND COLOUR RANGE



Appin Stone



Basalt

Colours displayed in this brochure are to be used as a guide only. Colours are as close as printing process will allow. Displays in store may vary to actual colour due to batch variations. Obtain samples from Baines Masonry for current batch colour. Care should be taken to order sufficient products to complete job at one time to avoid batch variations. Surplus blocks are not returnable. No claims after seven (7) days or once products have been incorporated in construction.

Refer to Evaluation and Installation guide or website for specification. Check with your local Council to ensure all local building requirements are complied with.

Norfolk® is a registered trade mark of Baines Masonry and is used under licence. Please see our full terms and conditions on our website.



**BAINES
MASONRY**
Quality First

900 Wilton Road (PO Box 89)
Appin NSW 2560

T. 02 4631 1383

info@bainesmasonry.com.au
www.bainesmasonry.com.au